Ì,

## Listing of Claims:

This listing of claims reflects all claim amendments and replaces all prior versions, and listings, of claims in the application. Material to be inserted is in <u>underline</u>, and material to be deleted is in <u>strikeout</u> or (if the deletion is of five or fewer consecutive characters or would be difficult to see) in double brackets [[ ]]. Any cancellations are without prejudice.

RECEIVED
CENTRAL PAX CENTER

1-6. (Canceled)

JAN 2 4 2005

7. (Currently amended) A small watercraft comprising:

an engine <u>disposed such that an axial direction of a crankshaft thereof</u>

<u>substantially corresponds with a front-rear direction of the watercraft, for propelling</u>

<u>the engine being configured to propel</u> a body of the watercraft;

an oil tank <u>provided below the engine such that a longitudinal direction of the</u>

<u>oil tank substantially corresponds with the front-rear direction of the body, the oil</u>

<u>tank being configured to reserve oil for lubricating the engine;</u>

an oil separator configured to separate the oil from a blow-by gas of the engine; and

an oil return passage configured to return the separated oil to the oil tank through an oil pipe[[,]]; wherein

the oil return passage is configured to open in the oil tank in a direction substantially perpendicular to a front-rear direction of the watercraft.

Page 2 - RESPONSE TO OFFICE ACTION Serial No. 10/646,956 2,

wherein one end of the oil pipe is connected to the separator and an opposite
end thereof is connected to a return port provided on a rear wall of the oil tank; and

wherein the return port has a rear end connected to the oil pipe and is provided with a first hole extending forward in the front-rear direction of the watercraft and substantially horizontally from the rear end, and a second hole extending from the first hole in a direction to form substantially a right angle with respect to the first hole and is configured to have an opening which opens in a direction to form substantially a right angle with respect to the longitudinal direction of the oil tank within the oil tank.

- 8. (Canceled)
- 9. (New) The small watercraft according to claim 7, wherein a baffle member is provided in the vicinity of the second hole within the oil tank to extend substantially in parallel with the second hole and to cover a region in front of the opening of the second hole from a forward side of the opening, relative to the front-rear direction of the watercraft.
- 10. (New) The small watercraft according to claim 7, wherein the second hole is configured to extend substantially vertically from the first hole and to open upwardly.
- Page 3 RESPONSE TO OFFICE ACTION Serial No. 10/646,956

- D .
- 11. (New) The small watercraft according to claim 10, wherein the baffle member is provided to extend from a bottom wall of the oil tank beyond the opening of the second hole.
- 12. (New) A small watercraft comprising:

  an engine configured to propel a body of the watercraft;

  an oil tank configured to reserve oil for lubricating the engine;

  an oil separator configured to separate the oil from a blow-by gas of the engine;

  and

an oil return passage configured to return the separated oil to the oil tank through an oil pipe;

wherein one end of the oil pipe is connected to the separator and an opposite end thereof is connected to a return port provided on a rear wall of the oil tank; and

wherein the return port is configured to guide oil through a wall of the oil tank in a first direction, and release oil into the tank in a second direction that is different from the first direction.

- 13. (New) The small watercraft of Claim 12, wherein the return port includes an upstream end that is connected to the oil pipe and configured to guide oil into the tank in a first direction, a bend formed within the oil tank and downstream of the upstream end that is configured to change a flow direction of the oil flowing into the oil tank, and a
- Page 4 RESPONSE TO OFFICE ACTION Serial No. 10/646,956

4)

downstream end formed downstream of the bend, which is configured to release the oil into the oil tank in a second direction that is different from the first direction.

- 14. (New) The small watercraft of Claim 13, wherein the first and second directions are oriented at substantially a right angle relative to each other.
- 15. (New) The small water craft of Claim 12, further comprising:

  a baffle member positioned within the oil tank adjacent a downstream end of the return port.
- 16. (New) The small water craft of Claim 15, wherein the baffle member is formed in a location such that the downstream end of the return port is positioned intermediate the baffle member and the upstream end of the return port.
- 17. (New) The small water craft of Claim 16, wherein the baffle member is extended along an axial direction of the downstream end of the return port.
- 18. (New) The small water craft of Claim 17, wherein the baffle member includes a surface that is substantially orthogonal to the first direction of oil flow.

Page 5 - RESPONSE TO OFFICE ACTION Serial No. 10/646,956